

monty® **Universal 2**

certified by wdk for handling UHP and run-flat tyres

*Demounting
without
tyre lever*



Tyre changers with
semi-automatic
demounting procedure

The all-rounder



Today many cars are equipped with UHP or run-flat tyres. While improving vehicle safety those tyres have rather rigid sidewalls, which is a big challenge both to mounting and demounting equipment and operators.

Especially in bead breaking operations major forces are required, involving a considerable risk to damage the tyre. The tyre changers of series monty universal 2 were specially designed to handle such tyres in that their special design perfectly supports mounting and demounting operations.

The special handling capability of the machine for UHP and run-flat tyres is certified by wdk (Association of German Tyre Industry).

In addition the tyre changer is also ideally suited for handling tyres of all types, covering the wide range of rims up to 30" diameter and 17" width.

Bead breaking

The monty universal 2 is designed for bead breaking on both sides with a roller-type tool without need to turn the wheel over and clamp again.

Bead breaking of the upper bead is accomplished with the plastic bead breaker disc in a continuous process while the wheel is slowly rotated.



As soon as the disc is below the rim flange, a button on the control console is pressed to optimise the angle of application of the disc and to ensure optimum introduction of bead breaking forces into the bead – a more gentle and user-friendly operation is hardly possible.

For bead breaking of the lower bead the bead breaker disc is hinged by 180 deg. and positioned under the lower bead which is then also broken at an optimum angle of the disc – hence most gently and preserving to the tyre.

Integrated demounting finger



The monty universal 2 is equipped with an automatic integrated demounting finger which supersedes the conventional tyre lever, pulling the bead over the rim flange as gentle to the tyre as can be and doing the otherwise tedious job of the operator.

The all-rounder



Wheel lift


The ergonomic wheel lift is especially useful when it comes to clamping very large and heavy wheels and – best of all – it comes standard with the tyre changer.



wheel types and even reverse mounted wheels can be handled ergonomically and conveniently.

Control console

Equipped with all essential controls the control console is in ergonomic position for the operator to control and supervise all individual operations.



Central clamping

With the central clamping flange the rim is clamped by its centre bore, hence little effort is required to centre every wheel before breaking upper and lower beads without additional work.

The clamping flange is vertically adjustable so that a large variety of



Clamping flange speed can be chosen according to requirements: slow speed is ideally suited for accurate and attentive operation in critical phases such as bead breaking and pulling the bead over the rim, whereas quick speed allows to save time in uncritical phases.

GP version

Includes the external bead seating device to facilitate bead seating and inflation of tubeless tyres.

Optional extras



4030486 – **Light-truck wheel kit**
To clamp light-truck wheels



4031245 – **Reverse mounting kit**
To clamp reverse mounted wheels



4030515 – **Closed centre rim kit**
To clamp closed centre rims, including compact clamping device



4030849 – **Laser pointer**
To facilitate correct positioning of the mounting head

Technical data and dimensions		
Clamping range	inch	12 – 30
Max. rim width	inch	17
Max. tyre width	inch	17
Max. wheel diameter	mm	1200
Wheel weight	kg	70
Clamping flange speed	rpm	7 / 13
Dimensions max. (W x D x H)	mm	1600 x 1520 x 2100
Machine weight incl. wheel lift	kg	430 / GP: 450
Operating pressure	bar	8 – 12
Power supply		200 – 240 V 1ph 50/60 Hz

Snap-on Equipment

France

Snap-on Equipment France · ZA du Vert Galant · 15, rue de la Guivernone BP97175
ST Ouen L'Aumone · 95056 Cergy Pontoise Cedex
Phone: +33 (0) 134/48 58-78 · Fax: +33 (0) 134/48 58-70 · www.snapon-equipment.fr

Germany

Snap-on Equipment GmbH · Konrad-Zuse-Straße 1 · 84579 Unterneukirchen
Phone: +49 (0) 8634/622-0 · Fax: +49 (0) 8634/5501 · www.snapon-equipment.de

Italy

Snap-on Equipment s.r.l. · Via Prov. Carpi, 33 · 42015 Correggio (RE)
Phone: +39 0522/733-411 · Fax: +39 0522/733-410 · www.snapon-equipment.eu

United Kingdom

Snap-on Equipment Ltd. · 48 Sutton Park Avenue · Reading RG6 1AZ
Phone: +44 (0) 118/929-6811 · Fax: +44 (0) 118/966-4369 · www.snapon-equipment.co.uk

EMEA-JA

Snap-on Equipment s.r.l. · Via Prov. Carpi, 33 · 42015 Correggio (RE)
Phone: +39 0522/733-411 · Fax: +39 0522/733-479 · www.snapon-equipment.eu

Part of the machines is illustrated with optional extras available at extra cost.
Technical modifications reserved.

Cod.: 9702 117 · 10/2010